

DLQ5 series

Introduction

- Comply with JONHON standard Q / 21EJ2656.
- Plastic housing, direct push-pull locking structure for plug and receptacle with high pressure interlocking, waterproof, secondary separation and other functions. Mini type, small size and light weight.



Application

Used for strong current connection of PDU, all-in-one controller and battery box.

Main technical performance

Rated current: 200A

Rated voltage: 690V AC / 750V DC

Working temp: -40 °C ~ 125 °C

IP degree: IP68, IPXXB, IPXXD

Ordering information

[Plug]

Series name	DLQ5	-	T	200	G001
Separator	-				
Plug / receptacle type	T: plug				
Fuse gauge	100A, 125A, 160A, 200A, 250A, 315A, 350A, 400A				
Separator					
Modification	Default: Bassmann fuse G001: medium melting fuse				

[Receptacle]

Series name	DLQ5	-	Z	-	X	(L=300)	-	01
Separator	-							
Plug / receptacle type	Z: receptacle							
Separator	-							
Mounting type	X: mounting error proofing							
Length of signal line	Default: length is 220	(L = 300): length is 300						
Separator	-							
Modification	01, 02.....							

Example

DLQ5-T200 G001: DLQ5 series 200A, 750V DC (medium melting) fuse plug

Recommended models

No. of core	Appearance	Model list	Product description
/		DLQ5-T	No fuse
		DLQ5-T200	200A, 700V DC (Bassmann) fuse plug
		DLQ5-T250	250A, 700V DC (Bassmann) fuse plug
		DLQ5-T315	315A, 700V DC (Bassmann) fuse plug
		DLQ5-T350	350A, 600V DC (Bassmann) fuse plug
		DLQ5-T400	400A, 600V DC (Bassmann) fuse plug
		DLQ5-T200 G001	200A, 750V DC (medium melting) fuse plug
		DLQ5-T250 G001	250A, 750V DC (medium melting) fuse plug
		DLQ5-T315 G001	315A, 750V DC (medium melting) fuse plug
		DLQ5-T350 G001	350A, 750V DC (medium melting) fuse plug
		DLQ5-T400 G001	400A, 750V DC (medium melting) fuse plug
		DLQ5-Z	MSD receptacle
		DLQ5-Z-B	Back mounting MSD receptacle